Dräger

Dräger X-am[®] 5100 Single-Gas Detection Device

For manufacturing petrochemical products, aseptic packing, or handling of rocket fuel: the Dräger X-am[®] 5100 portable single-gas detector ensures that you use the safest methods possible for handling HF, HCl, H_2O_2 or hydrazine – thanks to proven Dräger sensor technology and a device design which is perfectly customised to reactive gases.



Dräger. Technology for Life®

Benefits

Ergonomic shape

The Dräger X-am 5100 features a lightweight, convenient smartphone format for the greatest level of comfort. The gas detection device has been pared down to the minimum and, thanks to its two-button control panel and simple menu navigation, it is intuitive to use.

Reliable handling of reactive gases

The X-am 5100 measures continuously and reliably HF, HCl, H₂O₂ or hydrazine and gives three kinds of warnings: visual (360°), acoustic (multi-tone alarm) and vibration.

Special device design

The special device design with direct gas entry ensures that the sensors react quickly. Plus, the device provides precise measurement data by avoiding gas adsorption in the device housing.

Robust design

The X-am 5100 is tough: the integrated rubber boot as well as the shock-resistant sensors offer extra safety in case of impact or vibrations. The gas detection device is also resistant to electromagnetic irradiation.

Area monitoring

Combined with the Dräger X-zone 5500, the gas detection device can be used for flexible area monitoring. For example, up to 25 X-zone 5500 units can be automatically connected to form a wireless alarm chain. This connection of the transportable 'measuring heads' allows for the monitoring of large areas such as pipelines or tanks during an industrial shutdown.

System Components



DrägerSensor XS

DrägerSensors can be used for detecting many different gases and vapours. We develop and produce the DrägerSensors ourselves. Additionally, you benefit from the sensors' long service life and low operating costs.

Statecombi

Dräger X-zone® 5500

State-of-the-art area monitoring – the Dräger X-zone[®] 5500 in combination with the Dräger X-am[®] 5000, 5100 or 5600 gas detection instruments can be used for the measurement of up to six gases and extends the portable gas detection technology to a comprehensive system with many applications.

Accessories

D-4946-2014



Dräger Configuration and Evaluation Software

Save measurement results, professionally configure gas detection instruments and viewing performance data – all that is possible with the tailor-made Dräger software.

Accessories



Calibration Gas and Accessories

Calibration of equipment will ensure safe operation and functionality of equipment and will also meet with the applicable regulations and codes of practice. Various calibration gas options are easily available.

Rechargeable battery and charging technology set



Vehicle charger mounting kit for a Dräger X-am[®] 1/2/5x00 charging module

Services



Product Service

Our product service department supports you with a range of service packages – in our shops or on site in your plant. Care, servicing and maintenance are key factors when it comes to safety. Diligent maintenance and care is also absolutely necessary from an economics perspective. Preventive checks, service procedures and original replacement parts make your investment last longer.

Training



The Dräger Academy has imparted well-founded and practical knowledge for over 40 years. With over 110 authorized trainers and more than 600 available topics, we conduct more than 2,400 training sessions per year. We equip your employees with the knowledge required for real-life situations and ensure that the learned material can be recalled and applied reliably – in their everyday work and especially in stressful situations. To meet your needs, we are also happy to develop a customized training program specifically for you.

Rental Service

From bridging a temporary shortage of equipment to procuring special equipment for applications involving specific requirements: If you only need to cover a temporary higher demand, then Dräger Rental Service with over 65,000 pieces of rental equipment is an economical alternative to purchasing. Fast, straightforward and with a wide range of additional services available upon request.



D-2330-2016

On-site Safety Service

Whether through a rental shop, personnel services or comprehensive safety management, our On-Site Safety Services provide support in all projects where there are particular safety risks – not to mention normal day-to-day business.

Related Products



Dräger Pac[®] 6000

The disposable personal single-gas detection device, Dräger Pac[®] 6000, measures CO, H₂S, SO₂ or O₂ reliably and precisely, even in the toughest conditions. The robust design, quick sensor response times, and a powerful battery ensure maximum safety for up to two years with virtually no maintenance required.

CLU UN CK Dräger co

D-4987-2017

4989-2017

Dräger Pac[®] 6500

The robust Dräger Pac[®] 6500 is your reliable companion under tough conditions. The personal single-gas detection device measures CO, H_2S , SO_2 or O_2 quickly and precisely. Quick sensor response times and a powerful battery also ensure safety.

Dräger Pac[®] 8000

With the robust Dräger Pac[®] 8000, you'll be well equipped for tough conditions: this non-disposable, personal single-gas detection device is a reliable and precise instrument, which detects hazardous concentrations of 29 different gases, including special gases like NO₂, O₃ or COCl₂.



Dräger Pac[®] 8500

The Dräger Pac[®] 8500 single-gas detection device is a reliable and precise instrument even under the toughest of conditions. The device can be equipped with a hydrogen-compensated CO sensor or a Dräger dual sensor. This gives you the option of measuring two gases at once: either H_2S with CO or O_2 with CO.

Technical Data

Dimensions (W x H x D)	48 x 130 x 61 mm; 1.89 x 5.12 x 2.4 inches			
Weight	220 – 250 g; 7.8 – 8.8 oz.			
Ambient conditions	Temperature	-20 to +50 °C; -4 to +122 °F		
	Pressure	700 to 1,300 mbar		
	Relative humidity	10 to 90 % r.h.		
Alarms	Visual	360°		
	Audible	Multi-tone > 90 dB at 30 cm; 1 ft.		
	Vibration			
Ingress Protection	IP54			
Operating times	~180 h (alkaline battery), ~150 h (NiMH rechargeable battery), or			
	~180 h (NiMH high capacity rechargeable battery)			
Charging times	< 4 h			
Data logger	Can be read out via infrared interface			
	> 1,000 h at a recording interval of 1 value per minute			
Approvals	ATEX	I M1 Ex ia I Ma		
		II 1G Ex ia IIC T4/T3 Ga		
		-20 °C ≤ Ta ≤ +55 /40 °C		
	IECEx	Ex ia I Ma		
		Ex ia IIC T4/T3 Ga		
		-20 °C ≤ Ta ≤ +55 /40 °C		
	_c CSA _{us}	Class I, Div. 1, Groups A,B,C,D TC T4/T3		
		Class I, Zone 0, A/Ex ia IIC T4/T3 /Ga		
	EAC Ex	PO Ex ia I X		
		0 Ex ia IIC T4/T3 X		
CE mark	Electromagnetic compatibility – Directive 2014/30/EU			
	Explosion protection – Directive 2014/34/EU			

Ordering Information

Dräger X-am [®] 5100			83 22 750		
Consisting of: basic dev	ice with an integrated data	a logger, manufa	cturer's certifie	cate and calibration certific	cate
A power pack and sense	or are integral elements of	a functioning de	evice		
Description	Measuring range	Resolution		Response time (t ₉₀)	Ordering no.
DrägerSensor XS EC HF/HCl	0 – 30 ppm	0.1 ppm		60 sec.*	68 09 140
DrägerSensor XS EC	0 – 20 ppm	0.1 ppm		60 sec.	68 09 170
H ₂ O ₂					
DrägerSensor XS EC	0 – 3 ppm	0.01 ppm		180 sec.	68 09 190
Hydrazin					
*Response time (t ₅₀)					
Power supply units					
NiMH power pack T4 (~150 h operating time)			83 18 704		
NiMH power pack T4 high capacity (~180 h operating time)			83 22 244		
Alkaline power pack T3/T4 (without alkaline batteries)			83 22 237		
Alkaline batteries T3 (2 pcs.) for alkaline power pack 83 22 237			83 22 239		
(~180 h operating time)					

Ordering Information

Charging accessories			
Charging module	83 18 639		
Rechargeable battery and charging technology set Consisting of: NiMH power pack T4, charging module, single	83 18 785		
charger (worldwide) for 1 charging module Rechargeable battery and charging technology set HC Consisting of: NiMH power pack T4 high capacity, charging module, single charger (worldwide) for 1 charging module	83 22 785		
Charging kit consisting of a charging module and a single charger (worldwide)	83 20 333		
Vehicle charging connecting cable 12 V / 24 V for charging module	45 30 057		
Vehicle charger mounting kit for a Dräger X-am [®] 1/2/5x00 charging module	83 18 779		
Calibration accessories			
Calibration adapter	68 06 291		
HCl test gas (10 ppm) for sensor 68 09 140	68 12 107		
HCl test gas (25 ppm) for sensor 68 09 140	68 12 115		
SO ₂ test gas (10 ppm) for sensor 68 09 170	68 10 645		
Accessories for measured value data logger and configuration			
Dräger GasVision 7	83 25 646		
Dräger CC-Vision Basic	free of charge: www.draeger.com/software		
USB DIRA with USB cable, infrared communication adapter to USB	83 17 409		

Not all products, features, or services are for sale in all countries.

Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA Moislinger Allee 53–55 23558 Lübeck, Germany www.draeger.com

REGION DACH

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 info@draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA Revalstraße 1 23560 Lübeck, Germany Tel +49 451 882 0 Fax +49 451 882 2080 info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA Branch Office P.O. Box 505108 Dubai, United Arab Emirates Tel +971 4 4294 600 Fax +971 4 4294 699 contactuae@draeger.com

REGION ASIA PACIFIC Draeger Singapore Pte. Ltd. 25 International Business Park #04-20/21 German Centre Singapore 609916 Tel +65 6308 9400 Fax +65 6308 9401 asia.pacific@draeger.com

REGION CENTRAL

AND SOUTH AMERICA Dräger Panama S. de R.L. 59 East Street, Nuevo Paitilla House 30, San Francisco Town Panama City, Panama Tel +507 377 9100 Fax +507 377 9130 servicioalcliente@draeger.com

Locate your Regional Sales Representative at: www.draeger.com/contact

