

The G.Stop fall arrester is manufactured using precision machined components. The unit's internal components are manufactured using bronze, stainless steel and aluminium. This ensures complete reliability and high performance even in the harshest of environments, making the G.Stop fall arrester the perfect choice of safety equipment even for offshore and mining operations.

The G.Stop fall arrester offers the user full protection from falling whilst allowing complete mobility when working at height. Should a fall occur, the G.Stop's steel rope will be pulled out of the unit at an accelerating rate; when a rope speed of approximately 1.5m/sec is reached, the braking system is activated. Once activated, the fall is quickly and smoothly arrested, exerting minimal forces upon the user's body. When the load is released the rope automatically retracts back into the fall arrester.

The G.Stop fall arrester can be mounted vertically above the user or horizontally, in conjunction with a suitable anchorage point. It can also be used in conjunction with our G.Tripod.

- ♦ Manufactured in the UK
- ♦ Lightweight, aluminium casing
- ♦ Shock absorbing brake mechanism
- ♦ Stopping distance 0.6m to 1m
- ♦ Auto-lock karabiner with fall indicator

Item Code*	Max. Rope Length	MWL	Options
GSE507G	7m	136kg	Stainless steel rope.
GSE514G	14m		
GSE520G	20m		
GSE534G	34m		

* with galvanised steel rope(fitted as standard)

